

Client	Quantity
Project	Position

Snack GN counter 2 doors

Model: TP12/1BR-490 Cod: T10291000404



Technical data

Тор:	With top
Gross capacity:	177 lt
Temperature range:	-15°-22°C
Refrigerant unit:	remote
Cooling gas:	R452a (GWP=2.141)
Refrigerant Charge:	110g
Defrost:	Electric
Body height:	490 mm
Valve:	Supplied standard with solenoid
Dimensions:	1200×700×630 mm
Packing dimensions:	1395×800×998 mm
Voltage:	220-240 V - 50-60 Hz
Cooling capacity:	540 W*
*:	Evap30°C Cond. +55°C

Features

Standard equipment:	2 slides, 2 plastic coated GN1/1 shelves
Control:	Electronic, display flush with the panel
Doors:	2 doors, self-closing, reversible with 105° stop
Door gasket:	Magnetic, triple chamber and easily replaceable
Insulation:	60 mm thickness - CFC/HCFC free
Exterior/interior finishing:	Exterior interior and back in AISI 304 stainless steel. Base in colaminated steel.
Inner corners:	Rounded for easy cleaning and ensuring maximum hygiene
Handle:	Stainless steel AISI 304, 2 mm thick
Racks and slides:	Stainless steel AISI 304
Feets:	AISI 304 stainless steel adjustable h 100/150 mm
Cosmo:	Predisposed for Cosmo Hub connection

Snack refrigerated counter 2 doors, lenght 1200 mm, counter body height 490 mm, with top. Remote refrigeration unit, 5 heavy duty climatic class and R452a refrigerant gas. Temperature range -15°-22°C with ventilated refrigeration. Equipment: 1 GN1/1 plastic coated shelf. Each compartment can be configured with 1/1, 1/2+1/2 drawers. Anti-corrosion treated evaporator and electric defrosting. 60 mm insulation thickness - HFO with high insulation performance

and low environmental impact (CFC, HCFC, HFC free). AISI 304 stainless steel handle and magnetic triple chamber door gasket, easily replaceable. Reversible, self-closing door opening with 105° stop. AISI 304 stainless steel interior/exterior

including external back. Rounded inner corners for easy cleaning. The reinforced modular base in colaminated steel allows installation on wheels, feet, mobile or masonry plinths. Replaceable refrigerant system FSS - Fast Service System - for quick and easy service. Prepared for connection to Cosmo - wi-fi remote

supervision system - and ModBus/RTU Rs485 connection.

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.



Accessories and variants

Drawers 1/1
Drawers 1/2
Special size of technical compartment
Drawers 1/1
Drawers 1/2
Technical compartment on the left
Common technical compartment
Special size of technical compartment
Technical compartment on the left
Counters without a technical compartment
Lock with key for drawer 1/1
Common technical compartment
Counters without a technical compartment
Lock with key for drawer 1/2
RAL customisable colouring
Lock with key for drawer 1/1
Lock with key for drawer 1/2
Alimentazione frequenza 60Hz
Other special voltage

Predisp control	osition for connection to CO2 remote unit
Alimen	tazione frequenza 60Hz
Other s	pecial voltage
Remote	e condensing unit NT2178GK
Adjusta	ble feet h 145/195 mm
4 Swive	el and brake castors h 128 mm
Bracket	ts for GN pans for drawer
GN1/2	container + lids kit for drawer, h 150 mm
GN1/3	container + lids kit for drawer, h 150 mm
Bottles	shelf, stainless steel coating for shelf 350
Stainles	ss steel shelf GN1/1
Plastic	coated shelf GN1/1
Pair of	type C slides 505 mm
Serial ir	nterface, RS485 cable
Cosmo	cable connection kit
Cosmo	wifi connection kit
Remov	able plinth GN 2DR h 100 mm
Remov	able plinth GN 2DR h 150 mm


Remote unit technical data


Voltage:	220-240 V - 50 Hz
Cooling gas:	R452A
Gross weight:	25,7 Kg
Dimensions:	500×330×295 mm
Pipe delivery:	Ø 3/8"
Pipe suction:	Ø 3/8"
Packing dimensions:	540×345×310 mm
Cooling capacity:	Evap30°C Cond. +55°C


COSMO - wi-fi control

Cosmo is The Nice Kitchen's exclusive Wi-Fi technology that allows Coldline, Modular and Nevo appliances to be connected and monitored from a smartphone. The counter, connected with Cosmo kit via cable to a Cosmo hub (MODI, VISION, THAW.PRO, LEVTRONIC, QUBI) or with Cosmo Wi-Fi kit, can be monitored by the CosmoApp and receive alerts in case of abnormal operation.

Technical draw









In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.