


Client	Quantity
Project	Position

Display case for ingredients 2560 mm

Model: YP25/13NLR Cod: V42251100001





Technical data

Gross capacity:	106 lt
Temperature range:	+2°+10°C
Refrigerant unit:	remote
Cooling gas:	R452a (GWP=2.141)
Valve:	Supplied standard with solenoid
Dimensions:	2560×380×275 mm
Packing dimensions:	2620×450×473 mm
Voltage:	220-240 V - 50-60 Hz
Cooling capacity:	368 W*
*:	Evap10°C Cond. +55°C

Features

Control:	Electronic, display flush with the panel
Insulation:	30 mm thickness - CFC/HCFC free
Exterior/interior finishing:	Exterior and interior AISI 304 stainless steel.
Inner corners:	Rounded for easy cleaning and ensuring maximum hygiene
Cosmo:	Predisposed for Cosmo Hub connection

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.



Accessories and variants

Alimentazione frequenza 60Hz	
Other special voltage	
Remote condensing unit EMT6144GK	
Lid for overnight storage of ingredients GN1/3 2138x302x20	
2560 display case pans kit, GN1/3	
Wall clamps, 2 pieces	
Kit of 4 stainless steel feets	
Cosmo cable connection kit	
Cosmo wifi connection kit	
Pan GN1/2 325x265x150 mm	
Lid for GN1/2 pan	

Pan GN1/3 325x176x150 mm	
Lid for GN1/3 pan	
Pan GN1/6 176x162x150 mm	
Lid for GN1/6 pan	
Pan GN1/9 176x108x100 mm	
Lid for GN1/9 pan	
Pan GN2/8 325x132x150 mm	
Lid for GN2/8 pan	
Brackets for pans 20 mm GN1/3	
Brackets for pans 25 mm GN1/3	
Brackets for pans 30 mm GN1/3	


Remote unit technical data

Voltage:	220-240 V - 50 Hz
Cooling gas:	R404-R452
Gross weight:	17 Kg
Dimensions:	450×300×270 mm
Pipe delivery:	Ø 1/4"
Pipe suction:	Ø 3/8"
Packing dimensions:	470×330×300 mm
Cooling capacity:	Evap10°C Cond. +55°C


COSMO - wi-fi control

Cosmo is The Nice Kitchen's exclusive Wi-Fi technology that allows Coldline, Modular and Nevo appliances to be connected and monitored from a smartphone. The display case for ingredients, connected with Cosmo kit via cable to a Cosmo hub (MODI, VISION, THAW.PRO, LEVTRONIC, QUBI) or with Cosmo Wi-Fi kit, can be monitored by the CosmoApp and receive alerts in case of abnormal operation.

Technical draw







A: Power supply cable outlet

B:

Condensation water drain

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.