Client _____ Quantity _____

Project _____ Position _____

Vision Industry W40K F

Model: W40KFR **Cod:** W81120112002



Vision Industry W40 trolley blast chiller Roll-In F version, temperature range -40°+65°C with humidifier boiler as standard. It is equipped with the functions: blast chilling, blast freezing, manual cycle, thawing, proving, retarded proving, holding, steam sanitising. Remote cooling system with R452a refrigerant gas. Devote™ - Dynamic Evolution Temperature - the innovative system that autonomously recognises the weight, size and temperature of food and automatically shortens the blast chilling or freezing time of hot food without the use of a core probe. 7" touch screen and operating mode with customisable recipes, by time, with core probe or with Devote algorithm. Adjustable ventilation 25-100%, adjustable humidity 45-95%. Blast chilling yield +90/+3°C - 120 Kg; blast freezing yield +90/-18°C - 90 Kg. 5 heavy duty climatic class, forced air defrost. 100 mm insulation thickness - HFO with high insulation performance and low environmental impact (CFC, HCFC, HFC free). Electronic expansion valve and anti-corrosion painted evaporator. Compensation valve to reduce waiting times during frequent door openings. Easily replaceable triple chamber magnetic gasket, core probe with screw connector and led lighting. Exterior and interior AISI 304 stainless steel, interior made of "canvas" steel with special highly durable texture. fan unit and condenser cover removable without tools. Blast chiller supplied assembled. ModBus/RTU Rs485 connection as standard. Cosmo: wi-fi connection for remote monitoring via Cosmo App. When wired to Coldline counters and cabinets acts as a hub for remote monitoring of connected equipment.

Technical data

Max capacity:	1 trolley
Temperature range:	-40°+65°C
Ventilation range:	25% - 100%
Humidity range:	45% - 95% with humidifier
Humidifier:	Including
Refrigerant unit:	remote
Yield +90/+3:	120 Kg
Yield +90/-18:	90 Kg
Cooling gas:	R404/R452
Defrost:	Forced air
Valve:	Electronic expansion valve
Dimensions:	1480×1430×2510 mm
Packing dimensions:	1620×1700×2550 mm
Voltage:	400-415 V - 50-60 Hz
Cooling capacity:	13170 W*
*:	Evap. -10°C Cond. +45°C

Features

Functions:	Blast chilling, shock freezing, thawing, proving and retarder prover, holding, steam sanitizing, manualcycle
Control:	7" touch screen display with USB port
Door gasket:	Magnetic, triple chamber and easily replaceable
Core probe:	Needle probe with 1 reading point, quick-release and easily replaceable
Insulation:	100 mm thickness - CFC/HCFC free
Exterior/interior finishing:	Internal and external in “linen canvas” steel
Inner corners:	Rounded base 20 mm
Handle:	In AISI 304 stainless steel
Cosmo:	Wi-Fi remote control system

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previosly or subsequently sold.

Accessories and variants

- Abbattitore fornito smontato
- Floor 20 mm high, ramp included
- Reverse door opening from standard
- Door opening turning and control panel inversion
- Door stop 100°
- Sonda al cuore 3 punti di lettura
- Sonda al cuore riscaldata 1 punto di lettura
- Winter kit -20°C
- Winter kit -40°C
- Other special voltage
- Open remote condensing unit 4CES-6Y
- Silenced faired remote condensing unit 4CES-6Y
- Faired unit with remote condenser 4CES-6Y
- PVC ventilation profiles W40K
- Ramp 100 mm high. Length 913 mm W40
- Ramp 140 mm high. Length 1390 mm W40
- Trolley GN1/1 20 trays 598x530x1630 mm
- Trolley EN60x40 20 trays 460x620x1750 mm
- Trolley GN2/1 20 trays 660x720x1750 mm
- Trolley EN60x80 20 trays 660x820x1750 mm
- Purity C Quell ST 50 filter cartridge
- Sanitizing detergent


Remote unit technical data

Voltage:	400-415 V 3N - 50 Hz
Cooling gas:	R404-R452a
HP unit:	6
Gross weight:	202 Kg
Dimensions:	1110×785×726 mm
Pipe delivery:	12 mm
Pipe suction:	35 mm
Cooling capacity:	Evap. -10°C Cond. +45°C

COSMO - wi-fi control

Cosmo is The Nice Kitchen's exclusive Wi-Fi technology that allows VISION blast chillers to be connected, updated and monitored from smartphones. VISION is also a Cosmo hub and allows remote supervision of the Coldline appliances connected to it. From the CosmoApp you can check the operating conditions of each machine and receive alerts in the event of abnormal operation.

Technical draw



A:	Power supply cable outlet	**B:**	Condensation water drain	**C:**	Floor grid for condensate drainage (recommended)
I:	Internal led lighting	**L:**	Door clear opening dimension	**N:**	PVC ventilation profiles
R:	Gas output pipes	**T:**	Pass-through version	**W:**	Water mains connection for humidifier - 3/4” female. Unloading not required

Energy consumption EN 10732

Blast chilling cycle +65/+10

Consumption	
Time	
Yield	120 Kg

Blast freezing cycle +65/-18

Consumption	
Time	
Yield	90 Kg

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previosly or subsequently sold.