

Client	Quantity	
5	` '	
Project	Position	

# Vision Industry W35K U

Model: W35KU Cod: W83110112002



Vision Industry W35 trolley blast chiller Roll-In U version, temperature range -40°+10°C. It is equipped with the functions: blast chilling, blast freezing, manual cycle. Plug-In refrigeration system with air condensation with R452a refrigerant gas. Devote  $^{\scriptscriptstyle\mathsf{TM}}$  - Dynamic Evolution Temperature - the innovative system that autonomously recognises the weight, size and temperature of food and automatically shortens the blast chilling or freezing time of hot food without the use of a core probe.  $7^{\circ}$  touch screen and operating mode with customisable recipes, by time, with core probe or with Devote algorithm. Adjustable ventilation 25-100%. Blast chilling yield +90/+3°C - 85 Kg; blast freezing yield +90/-18°C -60 Kg. 5 heavy duty climatic class, forced air defrost. 100 mm insulation thickness - HFO with high insulation performance and low environmental impact (CFC, HCFC, HFC free). Electronic expansion valve and anti-corrosion painted evaporator. Compensation valve to reduce waiting times during frequent door openings. Easily replaceable triple chamber magnetic gasket, core probe with screw connector and led lighting. Exterior and interior AISI 304 stainless steel, interior made of "canvas" steel with special highly durable texture. fan unit and condenser cover removable without tools. Blast chiller supplied assembled. ModBus/RTU Rs485 connection as standard. Cosmo: wi-fi connection for remote monitoring via Cosmo App. When wired to Coldline counters and cabinets acts as a hub for remote monitoring of connected equipment.

### **Technical data**

Max capacity:	1 trolley
Temperature range:	-40°+10°C
Ventilation range:	25% - 100%
Humidifier:	Not available
Refrigerant unit:	Plug-in
Yield +90/+3:	85 Kg
Yield +90/-18:	60 Kg
Climate class:	5
Cooling gas:	R404/R452
Defrost:	Forced air
Valve:	Electronic expansion valve
Dimensions:	1230×1200×2770 mm
Packing dimensions:	1464×1364×2550 mm
Voltage:	400-415 V - 50 Hz
Cooling capacity:	9100 W*
*:	Evap10°C Cond. +45°C

#### **Features**

Functions:	Blast chilling, shock freezing, continuous cycle
Control:	7" touch screen display with USB port
Door gasket:	Magnetic, triple chamber and easily replaceable
Core probe:	Needle probe with 1 reading point, quick-release and easily replaceable
Insulation:	100 mm thickness - CFC/HCFC free
Exterior/interior finishing:	Internal and external in "linen canvas" steel
Inner corners:	Rounded base 20 mm
Handle:	In AISI 304 stainless steel
Cosmo:	Wi-Fi remote control system

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.



## Accessories and variants

Abbattitore fornito smontato

Floor 20 mm high, ramp included

Reverse door opening from standard

Door opening turning and control panel inversion

Door stop 100°

Sonda al cuore 3 punti di lettura

Sonda al cuore riscaldata 1 punto di lettura

Winter kit -20°C

Winter kit -40°C

Other special voltage

PVC ventilation profiles W35K

Ramp 100 mm high. Length 913 mm W35

Ramp 140 mm high. Length 1390 mm W35

Trolley GN1/1 20 trays 598x530x1630 mm

Trolley EN60x40 20 trays 460x620x1750 mm

Purity C Quell ST 50 filter cartridge


Sanitizing detergent


Sterilizing UV lamp


# COSMO - wi-fi control

Cosmo is The Nice Kitchen's exclusive Wi-Fi technology that allows VISION blast chillers to be connected, updated and monitored from smartphones. VISION is also a Cosmo hub and allows remote supervision of the Coldline appliances connected to it. From the CosmoApp you can check the operating conditions of each machine and receive alerts in the event of abnormal operation.

### **Technical draw**







A: Power supply cable outlet

B: Condensation water drain

C: Floor grid for condensate drainage (recommended)

: Internal led lighting

Door clear opening dimension

N: PVC ventilation profiles

W: Water mains connection for humidifier - 3/4" female. Unloading not required

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.