

Client	Quantity
Project	Position

# Master Fish 350 cabinet

Model: A30/1P Cod: A14030300101



Master refrigerated Fish 350 cabinet, 1 door. Plug-in refrigeration unit, B energetic class, 5 heavy duty climatic class and R290 ecological refrigerant gas. Equipment: 3 GN1/1 ABS fish pans with false bottom, lock with key, led lighting, water drain. Temperature range -6°+40°C; ventilated refrigeration. Anti-corrosion treated evaporator, hot gas defrost. 75 mm insulation thickness - HFO with high insulation performance and low environmental impact (CFC, HCFC, HFC free). AISI 304 stainless steel handle and magnetic triple chamber door gasket, easily replaceable. Reversible, self-closing door opening with 105° stop. One-piece structure, interior/exterior AISI 304 stainless steel; outside back, external base and inside technical compartment in galvanised/colaminated steel. Rounded inner corners for easy cleaning. The reinforced modular base in colaminated steel allows installation on wheels, feet, mobile or masonry plinths. Replaceable refrigerant system FSS - Fast Service System - for quick and easy service. Predisposed for connection to Cosmo remote supervision system and ModBus/RTU Rs485 connection.

# **Technical data**

334 lt
-6°+4°C
Plug-in
В
33,1
324 kW/h annum
0,89 kW/h/24h
5
R290 (GWP=3)
75g
Hot gas
Supplied standard with solenoid
535×715×2085 mm
835×830×2144 mm
220-240 V - 50 Hz
406 W*
Evap10°C Cond. +55°C

## **Features**

Standard equipment:	3 slides for GN1/1 shelves, 3 abs GN1/1 pans, lock with key, LED lighting, water drain
Control:	Electronic, display flush with the panel
Doors:	1 door, self-closing with a 105° stop, right hinged
Door gasket:	Magnetic, triple chamber and easily replaceable
Insulation:	75 mm thickness - CFC/HCFC free
Exterior/interior finishing:	Exterior and interior AISI 304 stainless steel. Back, base and internal technical compartment in galvanized/colaminated steel.
Inner corners:	Rounded for easy cleaning and ensuring maximum hygiene
Handle:	Stainless steel AISI 304, 2 mm thick
Racks and slides:	Stainless steel AISI 304
Feets:	AISI 304 stainless steel adjustable h 100/150 mm
Cosmo:	Predisposed for Cosmo Hub connection

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previouly or subsequently sold.



## Accessories and variants

Special rack kit for drawers and shelves
Alimentazione frequenza 60Hz
Other special voltage
Frame for fixed masonry plinth
RAL customisable colouring
Master Marine solutions
Predisposition for connection to CO2 remote control unit
Foot pedal kit
4 Swivel and brake castors h 128 mm

Stainless steel shelf GN1/1
Plastic coated shelf GN1/1
Pair of type C slides 505 mm
Stainless steel drawer, h 150 mm 350
Bottles shelf, stainless steel coating for shelf 350
Serial interface, RS485 cable
Cosmo cable connection kit
Cosmo wifi connection kit
ABS fish pan GN1/1 with perforated false bottom


## Remote unit technical data


Voltage:	220-240 V - 50 Hz
Cooling gas:	R452A
Gross weight:	17 Kg
Dimensions:	450×300×270 mm
Packing dimensions:	470×330×300 mm
Cooling capacity:	Evap10°C Cond. +55°C


#### COSMO - wi-fi control

Cosmo is The Nice Kitchen's exclusive Wi-Fi technology that allows Coldline, Modular and Nevo appliances to be connected and monitored from a smartphone. The cabinet, connected with Cosmo kit via cable to a Cosmo hub (MODI, VISION, THAW.PRO, LEVTRONIC, QUBI) or with Cosmo Wi-Fi kit, can be monitored by the CosmoApp and receive alerts in case of abnormal operation.

## **Technical draw**









- A: Power supply cable outlet
- D: Airflow conveyor
- G: Racks pitch

P: Water drain

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.