

Client	Quantity
Project	Position

# Master GN counter 4 doors

Model: TA21/1B-710 Cod: T10402000401



# **Technical data**

T	With the end of other blands
Тор:	With top and splashback
Gross capacity:	599 lt
Temperature range:	-15°-22°C
Refrigerant unit:	Plug-in
Energetic class:	E
Energy efficiency index:	80,7
Annual consumption:	3642 kW/h annum
24h consumption:	9,978 kW/h/24h
Climate class:	5
Cooling gas:	R290 (GWP=3)
Refrigerant Charge:	110g
Defrost:	Hot gas
Body height:	710 mm
Valve:	Supplied standard with solenoid
Dimensions:	2260×700×950 mm
Packing dimensions:	2355×800×998 mm
Voltage:	220-240 V - 50 Hz
Cooling capacity:	569 W*
*:	Evap30°C Cond. +55°C

## **Features**

S	4 5 4 4 5 5 4 6 14 4 1 1
Standard equipment:	4 slides, 4 plastic coated GN1/1 shelves
Control:	Electronic, display flush with the panel
Doors:	4 doors, self-closing, reversible with 105° stop
Door gasket:	Magnetic, triple chamber and easily replaceable
Insulation:	60 mm thickness - CFC/HCFC free
Exterior/interior finishing:	Exterior interior and back in AISI 304 stainless steel. Base in colaminated steel.
Inner corners:	Rounded for easy cleaning and ensuring maximum hygiene
Handle:	Stainless steel AISI 304, 2 mm thick
Racks and slides:	Stainless steel AISI 304
Feets:	AISI 304 stainless steel adjustable h 100/150 mm
Cosmo:	Predisposed for Cosmo Hub connection

Master refrigerated counter 4 doors, counter body height 710 mm, top with splashback. Plug-in refrigeration unit, E energetic class, 5 heavy duty climatic class and R290 ecological refrigerant gas. Temperature range -15°-22°C with ventilated refrigeration. Equipment: 1 GN1/1 plastic coated shelf. Each compartment can be configured with 1/2+1/2, 1/3+2/3, 1/3+1/3+1/3 drawers. Anti-corrosion treated evaporator and hot gas defrosting. 60 mm insulation

thickness - HFO with high insulation performance and low environmental impact (CFC, HCFC, HFC free). AISI 304 stainless steel handle and magnetic triple chamber door gasket, easily replaceable. Reversible, self-closing door opening

with 105° stop. AISI 304 stainless steel interior/exterior including external back. Rounded inner corners for easy cleaning. The reinforced modular base in  $% \left\{ 1,2,...,n\right\}$ colaminated steel allows installation on wheels, feet, mobile or masonry plinths. Replaceable refrigerant system FSS - Fast Service System - for quick and easy service. Prepared for connection to Cosmo - wi-fi remote supervision system -

and ModBus/RTU Rs485 connection.

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.



### Accessories and variants


Drawers 1/2 Drawers 1/3 Drawers 1/3 + 2/3 Special counter body heights 650 mm Special counter body heights 700 mm Special counter body heights 750 mm Technical compartment on the left Lock with key for drawer 1/2 Lock with key for drawer 1/3 Lock with key for drawer 1/3 + 2/3 LED lighting RAL customisable colouring Plug-in water unit Alimentazione frequenza 60Hz Other special voltage Internal hygiene H3 Granite flat worktop


Granite worktop with splashback Service water sink Ø 300 mm Single lever mixer hole Ø 3/4 Adjustable feet h 145/195 mm 6 Swivel and brake castors h 128 mm Brackets for GN pans for drawer GN1/2 container + lids kit for drawer, h 150 mm GN1/3 container + lids kit for drawer, h 150 mm Bottles shelf, stainless steel coating for shelf 350 Stainless steel shelf GN1/1 Plastic coated shelf GN1/1 Pair of type C slides 505 mm Serial interface, RS485 cable Cosmo cable connection kit Cosmo wifi connection kit IP44 schuko socket with cover Removable plinth GN 4D h 100 mm


## COSMO - wi-fi control

Cosmo is The Nice Kitchen's exclusive Wi-Fi technology that allows Coldline, Modular and Nevo appliances to be connected and monitored from a smartphone. The counter, connected with Cosmo kit via cable to a Cosmo hub (MODI, VISION, THAW.PRO, LEVTRONIC, QUBI) or with Cosmo Wi-Fi kit, can be monitored by the CosmoApp and receive alerts in case of abnormal operation.

# **Technical draw**







A: Power supply cable outlet

B: Condensation water drain

Airflow conveyor

D:

G: Racks pitch

J: Automatic evaporation of condensing water

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.