

| Client  | Quantity |
|---------|----------|
| Project | Position |

# Pastry EN60x40 counter 2 doors

Model: TS13/1BJ-760 Cod: T20200000402



# **Technical data**

| Тор:                     | Without top                     |
|--------------------------|---------------------------------|
| ·                        |                                 |
| Gross capacity:          | 421 lt                          |
| Temperature range:       | -15°-22°C                       |
| Refrigerant unit:        | Plug-in                         |
| Energetic class:         | D                               |
| Energy efficiency index: | 74,7                            |
| Annual consumption:      | 2994 kW/h annum                 |
| 24h consumption:         | 8,203 kW/h/24h                  |
| Climate class:           | 5                               |
| Cooling gas:             | R290 (GWP=3)                    |
| Refrigerant Charge:      | 110g                            |
| Defrost:                 | Hot gas                         |
| Body height:             | 760 mm                          |
| Valve:                   | Supplied standard with solenoid |
| Dimensions:              | 1450×780×860 mm                 |
| Packing dimensions:      | 1545×900×998 mm                 |
| Voltage:                 | 220-240 V - 50 Hz               |
| Cooling capacity:        | 569 W*                          |
| *:                       | Evap30°C Cond. +55°C            |

# Pastry refrigerated counter 2 doors, counter body height 760 mm, without top. Plug-in refrigeration unit, D energetic class, 5 heavy duty climatic class and R290 ecological refrigerant gas. Temperature range -15°-22°C with ventilated refrigeration. Equipment: 8 pairs of slides for EN60x40 shelves. Each compartment can be configured with 1/2+1/2, 1/3+2/3, 1/3+1/3+1/3 drawers. Anti-corrosion treated evaporator and hot gas defrosting. 60 mm insulation thickness - HFO with high insulation performance and low environmental impact (CFC, HCFC, HFC free). AISI 304 stainless steel handle and magnetic triple chamber door gasket, easily replaceable. Reversible, self-closing door opening with 105° stop. AISI 304 stainless steel interior/exterior including external back. Rounded inner corners for easy cleaning. The reinforced modular base in colaminated steel allows installation on wheels, feet, mobile or masonry plinths. Replaceable refrigerant system FSS - Fast Service System - for quick and easy service. Prepared for connection to Cosmo - wi-fi remote supervision system - and ModBus/RTU Rs485 connection.

### **Features**

| Standard equipment:          | 8 slides EN60x40                                                                   |
|------------------------------|------------------------------------------------------------------------------------|
| Control:                     | Electronic, display flush with the panel                                           |
| Doors:                       | 2 doors, self-closing, reversible with 105° stop                                   |
| Door gasket:                 | Magnetic, triple chamber and easily replaceable                                    |
| Insulation:                  | 60 mm thickness - CFC/HCFC free                                                    |
| Exterior/interior finishing: | Exterior interior and back in AISI 304 stainless steel. Base in colaminated steel. |
| Inner corners:               | Rounded for easy cleaning and ensuring maximum hygiene                             |
| Handle:                      | Stainless steel AISI 304, 2 mm thick                                               |
| Racks and slides:            | Stainless steel AISI 304                                                           |
| Feets:                       | AISI 304 stainless steel adjustable h 100/150 mm                                   |
| Cosmo:                       | Predisposed for Cosmo Hub connection                                               |

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.



# Accessories and variants


| Drawers 1/2                        | Servi  |
|------------------------------------|--------|
| Drawers 1/3                        | Single |
| Drawers 1/3 + 2/3                  | Adjus  |
| Technical compartment on the left  | 4 Swi  |
| Lock with key for drawer 1/2       | Alum   |
| Lock with key for drawer 1/3       | Stainl |
| Lock with key for drawer 1/3 + 2/3 | Plasti |
| RAL customisable colouring         | Pair o |
| Plug-in water unit                 | IP44   |
| Alimentazione frequenza 60Hz       | Serial |
| Other special voltage              | Cosm   |
| Internal hygiene H3                | Cosm   |
| Granite flat worktop               | Remo   |
| Granite worktop with splashback    | Remo   |
|                                    |        |

| Single I | ever mixer hole Ø 3/4                |
|----------|--------------------------------------|
| Adjusta  | able feet h 145/195 mm               |
| 4 Swive  | el and brake castors h 128 mm        |
| Alumin   | ium coated backingan EN60x40 h 20 mm |
| Stainle  | ss steel shelf EN60x40               |
| Plastic  | coated shelf EN60x40                 |
| Pair of  | type L slides 605 mm                 |
| IP44 sc  | huko socket with cover               |
| Serial i | nterface, RS485 cable                |
| Cosmo    | cable connection kit                 |
| Cosmo    | wifi connection kit                  |
| Remov    | able plinth EN 2D h 100 mm           |
| Remov    | able plinth EN 2D h 150 mm           |

# COSMO - wi-fi control

Cosmo is The Nice Kitchen's exclusive Wi-Fi technology that allows Coldline, Modular and Nevo appliances to be connected and monitored from a smartphone. The counter, connected with Cosmo kit via cable to a Cosmo hub (MODI, VISION, THAW.PRO, LEVTRONIC, QUBI) or with Cosmo Wi-Fi kit, can be monitored by the CosmoApp and receive alerts in case of abnormal operation.

# **Technical draw**



A: Power supply cable outlet B: Condensation water drain

G: Racks pitch

J: Automatic evaporation of condensing water

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.