

Client \_\_\_\_\_ Quantity \_\_\_\_\_  
Project \_\_\_\_\_ Position \_\_\_\_\_

## Pastry EN60x40 counter 4 doors

Model: TP21/1BJ-660

Cod: T20401000403

Pastry refrigerated counter 4 doors, counter body height 660 mm, with top. Plug-in refrigeration unit, E energetic class, 5 heavy duty climatic class and R290 ecological refrigerant gas. Temperature range -15°-22°C with ventilated refrigeration. Equipment: 16 pairs of slides for EN60x40 shelves. Each compartment can be configured with 1/2+1/2, 1/3+2/3, 1/3+1/3+1/3 drawers. Anti-corrosion treated evaporator and hot gas defrosting. 60 mm insulation thickness - HFO with high insulation performance and low environmental impact (CFC, HCFC, HFC free). AISI 304 stainless steel handle and magnetic triple chamber door gasket, easily replaceable. Reversible, self-closing door opening with 105° stop. AISI 304 stainless steel interior/exterior including external back. Rounded inner corners for easy cleaning. The reinforced modular base in colaminated steel allows installation on wheels, feet, mobile or masonry plinths. Replaceable refrigerant system FSS - Fast Service System - for quick and easy service. Prepared for connection to Cosmo - wi-fi remote supervision system - and ModBus/RTU Rs485 connection.



### Technical data

|                          |                                 |
|--------------------------|---------------------------------|
| Top:                     | With top                        |
| Gross capacity:          | 757 lt                          |
| Temperature range:       | -15°-22°C                       |
| Refrigerant unit:        | Plug-in                         |
| Energetic class:         | E                               |
| Energy efficiency index: | 82,5                            |
| Annual consumption:      | 4182 kW/h annum                 |
| 24h consumption:         | 11,458 kW/h/24h                 |
| Climate class:           | 5                               |
| Cooling gas:             | R290 (GWP=3)                    |
| Defrost:                 | Hot gas                         |
| Body height:             | 660 mm                          |
| Valve:                   | Supplied standard with solenoid |
| Dimensions:              | 2560×800×800 mm                 |
| Packing dimensions:      | 2655×900×998 mm                 |
| Voltage:                 | 220-240 V - 50 Hz               |
| Cooling capacity:        | 569 W*                          |
| *:                       | Evap. -30°C Cond. +55°C         |

### Features

|                              |                                                                                    |
|------------------------------|------------------------------------------------------------------------------------|
| Standard equipment:          | 16 slides EN60x40                                                                  |
| Control:                     | Electronic, display flush with the panel                                           |
| Doors:                       | 4 doors, self-closing, reversible with 105° stop                                   |
| Door gasket:                 | Magnetic, triple chamber and easily replaceable                                    |
| Insulation:                  | 60 mm thickness - CFC/HCFC free                                                    |
| Exterior/interior finishing: | Exterior interior and back in AISI 304 stainless steel. Base in colaminated steel. |
| Inner corners:               | Rounded for easy cleaning and ensuring maximum hygiene                             |
| Handle:                      | Stainless steel AISI 304, 2 mm thick                                               |
| Racks and slides:            | Stainless steel AISI 304                                                           |
| Feets:                       | AISI 304 stainless steel adjustable h 100/150 mm                                   |
| Cosmo:                       | Predisposed for Cosmo Hub connection                                               |

|                                    |                                            |
|------------------------------------|--------------------------------------------|
| Drawers 1/2                        | Service water sink Ø 300 mm                |
| Drawers 1/3                        | Single lever mixer hole Ø 3/4              |
| Drawers 1/3 + 2/3                  | Adjustable feet h 145/195 mm               |
| Technical compartment on the left  | 6 Swivel and brake castors h 128 mm        |
| Lock with key for drawer 1/2       | Aluminium coated backingan EN60x40 h 20 mm |
| Lock with key for drawer 1/3       | Stainless steel shelf EN60x40              |
| Lock with key for drawer 1/3 + 2/3 | Plastic coated shelf EN60x40               |
| RAL customisable colouring         | Pair of type L slides 605 mm               |
| Plug-in water unit                 | IP44 schuko socket with cover              |
| Alimentazione frequenza 60Hz       | Serial interface, RS485 cable              |
| Other special voltage              | Cosmo cable connection kit                 |
| Internal hygiene H3                | Cosmo wifi connection kit                  |
| Granite flat worktop               | Removable plinth EN 4D h 100 mm            |
| Granite worktop with splashback    | Removable plinth EN 4D h 150 mm            |

Cosmo is The Nice Kitchen's exclusive Wi-Fi technology that allows Coldline, Modular and Nevo appliances to be connected and monitored from a smartphone. The counter, connected with Cosmo kit via cable to a Cosmo hub (MODI, VISION, THAW.PRO, LEVTRONIC, QUBI) or with Cosmo Wi-Fi kit, can be monitored by the CosmoApp and receive alerts in case of abnormal operation.

Technical drawings of the H10000 storage cabinet, showing front, top, and side views with dimensions and labels.

**Front View (Left):** Shows the overall dimensions and internal layout. The total width is 2560<sup>+4</sup><sub>0</sub>. The total height is 140. The cabinet is divided into four main sections: two H2 sections (each 1173 wide) and two H3 sections (each 2100 wide). The depth is 100. Labels A, B, C, D, and H1 are indicated.

**Top View (Middle):** Shows the top dimensions. The total width is 800. The distance between the inner sections is 780. The depth is 100. Labels A, B, C, D, and H1 are indicated.

**Side View (Right):** Shows the side dimensions. The total width is 2220. The distance between the inner sections is 780. The depth is 1300. Labels A, B, C, D, and H1 are indicated.

- |    |                           |    |                                           |    |                  |
|----|---------------------------|----|-------------------------------------------|----|------------------|
| A: | Power supply cable outlet | B: | Condensation water drain                  | D: | Airflow conveyor |
| G: | Racks pitch               | J: | Automatic evaporation of condensing water |    |                  |