

Client \_\_\_\_\_ Quantity \_\_\_\_\_  
Project \_\_\_\_\_ Position \_\_\_\_\_

## Pastry EN60x40 counter 4 doors

Model: TA21/1MJ-660

Cod: T20402000203

Pastry refrigerated counter 4 doors, counter body height 660 mm, top with splashback. Plug-in refrigeration unit, C energetic class, 5 heavy duty climatic class and R290 ecological refrigerant gas. Temperature range -2°+8°C with ventilated refrigeration. Equipment: 16 pairs of slides for EN60x40 shelves. Each compartment can be configured with 1/2+1/2, 1/3+2/3, 1/3+1/3+1/3 drawers. Anti-corrosion treated evaporator and hot gas defrosting. 60 mm insulation thickness - HFO with high insulation performance and low environmental impact (CFC, HCFC, HFC free). AISI 304 stainless steel handle and magnetic triple chamber door gasket, easily replaceable. Reversible, self-closing door opening with 105° stop. AISI 304 stainless steel interior/exterior including external back. Rounded inner corners for easy cleaning. The reinforced modular base in colaminated steel allows installation on wheels, feet, mobile or masonry plinths. Replaceable refrigerant system FSS - Fast Service System - for quick and easy service. Prepared for connection to Cosmo - wi-fi remote supervision system - and ModBus/RTU Rs485 connection.



### Technical data

|                          |                                 |
|--------------------------|---------------------------------|
| Top:                     | With top and splashback         |
| Gross capacity:          | 757 lt                          |
| Temperature range:       | -2°+8°C                         |
| Refrigerant unit:        | Plug-in                         |
| Energetic class:         | C                               |
| Energy efficiency index: | 35,5                            |
| Annual consumption:      | 1055 kW/h annum                 |
| 24h consumption:         | 2,89 kW/h/24h                   |
| Climate class:           | 5                               |
| Cooling gas:             | R290 (GWP=3)                    |
| Refrigerant Charge:      | 110g                            |
| Defrost:                 | Hot gas                         |
| Body height:             | 660 mm                          |
| Valve:                   | Supplied standard with solenoid |
| Dimensions:              | 2560×800×900 mm                 |
| Packing dimensions:      | 2655×900×998 mm                 |
| Voltage:                 | 220-240 V - 50 Hz               |
| Cooling capacity:        | 406 W*                          |
| *:                       | Evap. -10°C Cond. +55°C         |

### Features

|                              |                                                                                    |
|------------------------------|------------------------------------------------------------------------------------|
| Standard equipment:          | 16 slides EN60x40                                                                  |
| Control:                     | Electronic, display flush with the panel                                           |
| Doors:                       | 4 doors, self-closing, reversible with 105° stop                                   |
| Door gasket:                 | Magnetic, triple chamber and easily replaceable                                    |
| Insulation:                  | 60 mm thickness - CFC/HCFC free                                                    |
| Exterior/interior finishing: | Exterior interior and back in AISI 304 stainless steel. Base in colaminated steel. |
| Inner corners:               | Rounded for easy cleaning and ensuring maximum hygiene                             |
| Handle:                      | Stainless steel AISI 304, 2 mm thick                                               |
| Racks and slides:            | Stainless steel AISI 304                                                           |
| Feets:                       | AISI 304 stainless steel adjustable h 100/150 mm                                   |
| Cosmo:                       | Predisposed for Cosmo Hub connection                                               |

|                                    |                                            |
|------------------------------------|--------------------------------------------|
| Drawers 1/2                        | Granite worktop with splashback            |
| Drawers 1/3                        | Service water sink Ø 300 mm                |
| Drawers 1/3 + 2/3                  | Single lever mixer hole Ø 3/4              |
| Technical compartment on the left  | Adjustable feet h 145/195 mm               |
| Lock with key for drawer 1/2       | 6 Swivel and brake castors h 128 mm        |
| Lock with key for drawer 1/3       | Aluminium coated backingan EN60x40 h 20 mm |
| Lock with key for drawer 1/3 + 2/3 | Stainless steel shelf EN60x40              |
| RAL customisable colouring         | Plastic coated shelf EN60x40               |
| Plug-in water unit                 | Pair of type L slides 605 mm               |
| Stainless steel evaporator         | IP44 schuko socket with cover              |
| Alimentazione frequenza 60Hz       | Serial interface, RS485 cable              |
| Other special voltage              | Cosmo cable connection kit                 |
| Internal hygiene H3                | Cosmo wifi connection kit                  |
| Granite flat worktop               | Removable plinth EN 4D h 100 mm            |

Cosmo is The Nice Kitchen's exclusive Wi-Fi technology that allows Coldline, Modular and Nevo appliances to be connected and monitored from a smartphone. The counter, connected with Cosmo kit via cable to a Cosmo hub (MODI, VISION, THAW.PRO, LEVTRONIC, QUBI) or with Cosmo Wi-Fi kit, can be monitored by the CosmoApp and receive alerts in case of abnormal operation.

The technical drawings illustrate the dimensions and layout of the H10000 storage cabinet. The front view (left) shows a total width of 2560 mm (with a tolerance of +4 mm) and a height of 140 mm. The cabinet is divided into four compartments: two H2 compartments (each 1173 mm wide) and two H3 compartments (each 2100 mm high). The side view (middle) shows a total width of 800 mm and a height of 100 mm. It details the internal structure with dimensions such as 780 mm, 655 mm, and 67 mm. The top view (right) shows a total width of 2220 mm and a height of 1300 mm. It displays four EN 600x400 compartments, each 600 mm wide and 400 mm high, with a total height of 1350 mm. The top view also shows a total width of 300 mm and a height of 40 mm. Labels A, B, C, D, and J are used to identify specific components and features.

- |    |                           |    |                                           |    |                  |
|----|---------------------------|----|-------------------------------------------|----|------------------|
| A: | Power supply cable outlet | B: | Condensation water drain                  | D: | Airflow conveyor |
| G: | Racks pitch               | J: | Automatic evaporation of condensing water |    |                  |