

Client _____ Quantity _____
Project _____ Position _____

Modi Up Blast Chiller Counter

Model: WTA7UR

Cod: W17075012001

Modi counter multifunction blast chiller 7 trays Up version, top with splashback, temperature range -40°+10°C. It is equipped with the functions: blast chilling, blast freezing, manual cycle. Remote cooling system with R452a refrigerant gas. 4.3" touch screen and operating mode with customisable recipes, by time or with core probe. Adjustable ventilation 25-100%. Blast chilling yield +90/+3°C - 34 Kg; blast freezing yield +90/-18°C - 24 Kg. 5 heavy duty climatic class, forced air defrost. 60 mm insulation thickness - HFO with high insulation performance and low environmental impact (CFC, HCFC, HFC free). Electronic expansion valve and anti-corrosion painted evaporator. Easily replaceable triple chamber magnetic gasket and core probe with screw connector. Exterior and interior AISI 304 stainless steel. Equipment: 7 GN1/1-EN60x40 pairs of slides. ModBus/RTU Rs485 connection as standard. Cosmo: wi-fi connection for remote monitoring via Cosmo App. When wired to Coldline counters and cabinets acts as a hub for remote monitoring of connected equipment.



Technical data

Top:	Reinforced worktop with in order to place an oven
Gross capacity:	248 lt
Temperature range:	-40°+10°C
Ventilation range:	25% - 100%
Humidifier:	Not available
Refrigerant unit:	Plug-in
Yield +90/+3:	34 Kg
Yield +90/-18:	24 Kg
Cooling gas:	R452a (GWP=2.141)
Defrost:	Forced air
Body height:	710 mm
Valve:	Electronic expansion valve
Dimensions:	1400×700×950 mm
Packing dimensions:	1545×900×998 mm
Voltage:	220-240 V - 50-60 Hz
Cooling capacity:	2084 W*
*:	Evap. -10°C Cond. +45°C

Features

Functions:	Blast chilling, shock freezing, continuous cycle
Standard equipment:	7 slides GN1/1, EN60x40
Control:	4,3" touch screen display with USB port
Door gasket:	Magnetic, triple chamber and easily replaceable
Core probe:	Needle probe with 1 reading point, quick-release and easily replaceable
Insulation:	60 mm thickness - CFC/HCFC free
Exterior/interior finishing:	Exterior and interior AISI 304 stainless steel.
Inner corners:	Rounded for easy cleaning and ensuring maximum hygiene
Handle:	Stainless steel AISI 304, 2 mm thick
Racks and slides:	Stainless steel AISI 304, quick release
Feets:	AISI 304 stainless steel adjustable h 100/150 mm
Cosmo:	Wi-Fi remote control system

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.

Remote unit technical data

Voltage:	220-240 V - 50 Hz
Cooling gas:	R404-R452a
Gross weight:	25 Kg
Dimensions:	650×650×400 mm
Pipe delivery:	10 mm
Pipe suction:	10 mm
Cooling capacity:	Evap. -10°C Cond. +45°C

Cosmo is The Nice Kitchen's exclusive Wi-Fi technology that allows MODI blast chillers to be connected, updated and monitored from smartphones. MODI is also a Cosmo hub and allows remote supervision of the Coldline appliances connected to it. From the CosmoApp you can check the operating conditions of each machine and receive alerts in the event of abnormal operation.

Technical drawings of the EN 600x400 GN 530x325 unit, showing front, top, and side views with dimensions and drilling points.

Front View Dimensions:

- Overall width: 1400⁴
- Overall height: 140
- Internal width (excluding side panels): 605
- Internal height (excluding top and bottom panels): 710
- Top panel height: 60
- Bottom panel height: 530
- Side panel thickness: 75
- Drilling point (G) location: 75 from the side panel edge.
- Bottom panel height (150 max): 100
- Bottom panel width: 107
- Bottom panel depth: 1086
- Bottom panel offset: 207

Top View Dimensions:

- Overall width: 700
- Overall height: 950
- Internal width (excluding side panels): 680
- Internal height (excluding top and bottom panels): 710
- Top panel height: 20
- Bottom panel height: 40
- Side panel thickness: 100
- Drilling point (A) location: 83 from the side panel edge.
- Drilling point (B) location: 465 from the side panel edge.
- Drilling point (C) location: 67 from the side panel edge.
- Bottom panel width: 680
- Bottom panel depth: 100

Side View Dimensions:

- Overall width: 960
- Overall height: 1395
- Internal width (excluding side panels): 555
- Internal height (excluding top and bottom panels): 710
- Top panel height: 150
- Bottom panel height: 170
- Side panel thickness: 120
- Drilling point (A) location: 150 from the side panel edge.
- Drilling point (B) location: 170 from the side panel edge.
- Drilling point (C) location: 120 from the side panel edge.
- Bottom panel width: 70
- Bottom panel depth: 90

Drilling Points:

- (A) Foratura fianco, schiena e vano tecnico / Side, back and technical compartment drilling
- (B) Foratura fianco, schiena e vano tecnico / Side, back and technical compartment drilling
- (C) Foratura fianco, schiena e vano tecnico / Side, back and technical compartment drilling
- (G) Foratura fianco, schiena e vano tecnico / Side, back and technical compartment drilling

Other Dimensions:

- EN 600x400 GN 530x325
- 11,25
- x 4

- | | | | | | |
|----|---|----|--------------------------|----|-------------|
| A: | Power supply cable outlet | B: | Condensation water drain | G: | Racks pitch |
| J: | Automatic evaporation of condensing water | | | | |